

■Basic Specification

Max Load Capacity	kg	250
Platform Size(W×L×H)	mm	1,130×730×1,020
Platform Max Height	mm	13,015
Machine Weight(w/Pad)	kg	8,150(8,390)

■Size on Transportation

Total Length	mm	7,235
Total Width	mm	2,250
Total Height	mm	2,150

■Engine

Model		D1305
Category		Water Cooling 4 Cycle Diesel
Rated Output	kW/min <sup>-1</sup> (PS/rpm)	17.5/2,400(23.8/2,400)

■Mobility

Slewing Speed	sec/360°	55
Travel Speed(Low·High1·High2)	km/h	1.2/1.5/2.5
Max/Avg Ground Pressure	kPa (kgf/cm <sup>2</sup> )	100/39(1.02/0.40)
Max/Avg Ground Pressure(w/Pad)	kPa (kgf/cm <sup>2</sup> )	103/40(1.05/0.41)
Gradability Angle	% (°)	36(20)

■Tank

Hydraulic Oil Tank	ℓ	50
Fuel Tank	ℓ	100

■Working Hours

Boom(Up/Down)	sec	36/40
Extension(Expand/Contract)	sec	26.5/26
Platform Swing(Left/Right)	sec	15/15

■SAFETY SYSTEM

※1PS=0.75kW

- Emergency Stop Device ●Dead-man Device ●Holding Valve●Emergency Pump
- Operating Lever Pre-operation Preventing Device●Engine Starting Malfunction Preventing Device
- Warning Device●Horn●Slewing Lock Pin ●Safety Belt Hooking Device
- Travel Regulating Safety Device & Travel Mode Switch