

■Basic Specification

Max Load Capacity	kg	200
Platform Size(W×L×H)	mm	1,130×730×1,020
Platform Max Height	mm	17,950
Machine Weight(w/Pad)	kg	9,180(9,420)

■Size on Transportation

Total Length	mm	6,120
Total Width	mm	2,250
Total Height	mm	2,365

■Engine

Model		D1305
Category		Water Cooling 4 Cycle Diesel
Rated Output	kW/min ⁻¹ (PS/rpm)	17.5/2,400(23.8/2,400)

■Mobility

Slewing Speed	sec/360°	55
Travel Speed(Low·High1·High2)	km/h	0.5/1.6/2.9
Max/Avg Ground Pressure	kPa (kgf/cm ²)	106.4/44.4(1.08/0.45)
Max/Avg Ground Pressure(w/Pad)	kPa (kgf/cm ²)	107.2/45.5(1.09/0.46)
Gradability Angle	% (°)	36(20)

■Tank

Hydraulic Oil Tank	ℓ	50
Fuel Tank	ℓ	100

※1PS=0.75kW

■SAFETY SYSTEM

- Emergency Stop Device ●Dead-man Device ●Holding Valve
- Operating Lever Pre-operation Preventing Device ●Emergency Pump
- Engine Starting Malfunction Preventing Device
- Warming Device●Horn●Slewing Lock Pin ●Safety Belt Hooking Device
- Travel Regulating Safety Device & Travel Mode Switch